



P4200WPM Remote Dryer

- Air delivery up to 4,200 SCFD
- All-weather operation (-40° to 120° F) - thermostatically regulated internal climate controls
- Remote alarm monitoring capabilities of 6 points
- Slide-out compressor
- Rugged aluminum cabinet
- Quiet operation - only 48 dBA
- 8,000 hour maintenance interval

Accessories:

- Monitoring Interface (PVDW40)
- 6-Month Maintenance Kit (P011643)
- 8,000 Hour Maintenance Kit (P011763)
- 16,000 Hour Maintenance Kit (P011797)



Specifications

Output Capacity	Normal: Up to 2,600 SCFD continuous Maximum: 4,200 SCFD emergency
Power Requirements	110 - 125 VAC, 1 Phase, 60 Hz (20 Amp service recommended)
Running Amps	10 Amps
Outlet Pressure Range	0-15 PSIG
Outlet Air Relative Humidity	Less than 2% RH
Compressor Type	Two-cylinder, 3/4 HP, oil-less type
Drying Method	Heatless Desiccant
Operating Temperature Range	-40° to 120° F
Noise Level	48 dBA at 3'
Heat Dissipation	4,600 BTU/hr
Alarms	2 common alarm points + remote capabilities for 6 points
Outlet Connection	1/2" NPT Female
Dimensions	20.25" D x 17.5" W x 47.75" H
Net Weight / Shipping Weight	212 lbs / 233 lbs