



## P550W Series (Up to 350 SCFD continuous)

- Air delivery up to 550 SCFD
- Available in 120 VAC & 220 VAC models
- Remote real-time data and alarm reset capabilities
- SNMP communication compatible
- Digital display of all operating parameters
- 8,000 hour maintenance interval
- Compact and lightweight
- Versatile installation
- Ultra quiet compressor



### Accessories:

- Universal Rack Mounting Kit (P011674)
- Wall Mounting Kit (P011773)
- 6-Month Maintenance Kit (P011798)
- 8,000 Hour Maintenance Kit (P011673)
- Cycle Module Interface (P012341)
- 3/8" Tubing (PMP26A20 - sold per foot)

	120 VAC	220 VAC
Standard Pressure	<b>P550W</b>	<b>P552W</b>
Low Pressure	<b>P550WLP</b>	<b>P552WLP</b>
w/ 4-Port Outlet	<i>(above model #) + H</i>	
w/ Outdoor Enclosure	<i>(above model #) + X</i>	

### Specifications

	P550W Series	P552W Series
Output Capacity	Normal: Up to 350 SCFD continuous Maximum: 550 SCFD emergency	
Power Requirements	110 - 125 VAC, 50/60 Hz (15 Amp service recommended)	208 - 253 VAC, 50/60 Hz (15 Amp service recommended)
Running Amps	7.0 Amps	3.5 Amps
Outlet Pressure Range	Standard Pressure models : 2 - 15 PSIG Low Pressure models : 0.30 - 7.50 PSIG	
Outlet Air Relative Humidity	Less than 2% RH	
Compressor Type	Two-cylinder, 1/3 HP, oil-less type	
Dehydrating Method	Heatless Desiccant	
Operating Temperature Range	40° to 85° F (optimal) (Down to -40° F with Outdoor Enclosure kit)	
Noise Level	48 dBA at 10'	
Alarms	15+ fully monitored points including SNMP communication	
Outlet Connections	3/8" tube fitting	
Dimensions	12" D x 17.25" W x 27" H	
Net Weight	74 lbs	