



PEAT25 Emergency Worksite Trailer

- **On board 50 amp generator** powering 120 VAC and 240 VAC outlets
- **High pressure (tool) system** adjustable from 0-125 PSI
- **Low pressure (dry air) system** with adjustable regulator
- 42 gallon diesel fuel tank providing more than 24 hours of continuous run time
- Secure, weather tight enclosure
- Centralized control panel located curb side
- All access panels are lockable and keyed alike
- Customer labeling available



Accessories:

- Telescopic Worklights
- Flow Gauge
- Humidity Alarm
- Retractable Hose Reel
- Power Extension Cords
- Electric Brakes w/ DOT breakaway system

Specifications

Output Capacity	25,000 SCFD
Engine / Generator	12.5kw continuous, 120/240 VAC, Single phase, 60 Hz
Fuel Tank	42 gallon, certified, polyethylene
Run Time (% of load / Hours)	25% / 63 50% / 49 75% / 37 100% / 28
Electrical Outlets	(2) 120 VAC, 20 amp, duplex, GFI (1) 240 VAC, 30 amp, GFI
Outlet Pressure Range	Dry air system: 0 - 25 PSIG (adjustable) Tool air system: 0 - 125 PSIG (adjustable)
Outlet Air Relative Humidity	Less than 2% RH
Compressor Type	(3) Oil-less, 2 HP
Axle	E-Z lube, 3,500 lbs capacity
Springs	(4) Leaf, 2400 lbs capacity each
Wheels / Tires	15" mod. rims / P215/75R15
Trailer Lighting	Side markers - street & curb side, (2) amber at front, (2) red at rear Stop, Turn, and Run lights at rear
Dimensions	120" L x 68" W x 88" H (304.8 cm x 172.7 cm x 223.5 cm)
Net Weight	2750 lbs (1247.4 kgs)